

Standard Pressure Gauges

44/55/66EVO



Pressure and temperature



Standard Pressure Gauges
Direct Mounting
Bottom and Back Connection

Black Steel Case:
 Nominal Diameters
 40mm, 50mm and
 63mm

Applications

- Pneumatic and Hydraulic Circuits
- Compressors
- Filters
- Pressure Regulators

Standard Version: 40mm, 50mm, 63mm

Accuracy: Class 2.5 as EN 837-1

Case:	Black Steel.
Movement:	Brass.
Socket material:	Brass.
Window:	Polycarbonate.
Dial:	ABS, white with black markings.
Pointers:	Black Painted Aluminium
Elastic element:	Phosphor bronze.
Working pressure:	75% max of F.S.V
Ranges	Vacuum to 600 psi/bar


Ranges

40mm and 50mm Diameter				
Stock Ranges	PSI/BAR	INHG	1/8"BSPT	1/4"BSPT (50mm only)
-30/0		•	•	•
0-15	•		•	•
0-30	•		•	•
0-60	•		•	•
0-100	•		•	•
0-160	•		•	•
0-200	•		•	•
0-300	•		•	•
0-400	•		•	•

63mm Diameter			
Stock Ranges	PSI/BAR	INHG	1/4"BSPT
-30/0		•	•
0-15	•		•
0-30	•		•
0-60	•		•
0-100	•		•
0-160	•		•
0-200	•		•
0-300	•		•
0-400	•		•
0-600	•		•

Please Note: The above ranges are available ex-stock, we can offer other ranges (i.e single scale) and connections, delivery times upon request.

TYPES AND DIMENSIONS



TYPE R- stem mounting; bottom connection					TYPE P - stem mounting; back connection					
DS	Ø A	B	C	E	DS	Ø A	B	C	D	E
40	41.5	23.4	7.7	20.3	40	41.5	27	20.1	14	20.3
50	48.7	27	9.7	24.6	50	48.7	27	24.1	14	23.3
63	61.6	28	10	24.6	63	61.6	28	30.3	14	23.3

Options

- ABS Case
- Steel Case with Ring
- Chromium Plated Case and Ring
- Stainless Steel Case and Ring
- Chromium Plated Socket
- Special Connections
- Restrictor In Inlet
- Oxygen Service
- Accuracy 1.6%
- Glass Window

Please Note: Models in all stainless steel with 316 stainless steel wetted parts available.

EVO Instrumentation Ltd reserve the right to make any necessary modifications to the product.

EVO Instrumentation Ltd, 31a Coppice Trading Estate,
 Off Stourport Road, Kidderminster, Worcs, DY11 7QY,
 Tel: 01562 741212 Fax: 01562 741666
 Email: sales@evoinstrumentation.co.uk
 Web: www.evoinstrumentation.co.uk